

Please complete and send to: technical@rawlinspaints.com

Should you have any questions please contact our Technical Team on 0113 2455450 (opt. 2)

Contractor Name	
Contact Telephone	
Email Address	

Building Owner	
Site Address	
Contact Email	

Protection Required For Doors					
30 Minutes		Class B		Class 0	
60 Minutes		Class C		Class 1	

Is the protection for			
Own peace of mind		Required for Building Regulations	

About the Door (tick all that apply)				
Softwood		Hardwood		Other please describe
Fire Rated		Glazed		
Solid		Hollow		
Composite		Panelled		

Current Finish									
New/Bare		Painted		Varnish		Stained		Unknown sealed	
Waxed		Lacquer		Laminated		Veneer		Factory Finished	

Type of Finish Required							
Painted		Clear Finish		Stained Finish		Bare	

Colour (s) Required	
---------------------	--

Is the Project							
Dry Internal		Damp Internal		External		High Wear and Tear	

If you ticked External or Damp Internal. Is the area for protecting					
Prone to damp or moisture ingress		Open to the elements		A Swimming Pool	
Under construction		Coastal		Kitchen or Bathroom	

Notes :

To help us provide the correct specification please complete as much detail as possible on both pages

If you have different levels of protection please complete an enquiry form for each.

Please note that Class 1, 0, B, or C are not the same as 30 and 60 minutes fire resistance.

Please complete and send to: technical@rawlinspaints.com

Should you have any questions please contact our Technical Team on 0113 2455450 (opt. 2)

Door			
What is the measurement for the thickest part of the door			mm
What is the measurement of the thinnest part (panel) of the door			mm
How is the door glazed			
Is there an intumescent strip	In the door		In the frame
Surrounding Frame and Wall			
Has the wall been assessed for Fire Resistance			
Has the door frame been assessed for Fire Resistance			
Is the required compartmentation 30 or 60 minutes			
How is the wall constructed			
Concrete		Dry Lining	
Brick		Lath & Plaster	

Number of Doors to be protected (Complete a separate form for each different type of door)	
--	--

Survey Completed By	
Company Name	

Specification Issued By	
Specification Date	
Specifications are valid for 6 months from the specification date.	

Specification Number	
----------------------	--

DOORS

It is important to note that most modern internal doors cannot be upgraded to achieve 30 minutes Fire Resistance.

However, where installation of fire rated door sets is not an option due to listed building status or similar Thermoguard Timbercoat Insulating Basecoat and Thermoguard 2K Fire Varnish Basecoat with the correct topcoat are capable of upgrading doors under specific circumstances.

- Doors would be that can afford to lose 2mm to charring and
- Solid, joint-free doors with compressed core and a reasonable thickness (6 mm +), veneer faces bonded to either side of the core. These can be flush doors or pressed to create a moulded look.
- Well-seasoned, old or sturdy doors with 35mm + thick frames and panels 10mm + thick.

If you are unsure if your doors fulfil this criteria complete this form and return to technical@rawlinspaints.com or call 0113 2455450 (opt. 2) to discuss your project.

Contact information submitted will only be used for the purposes of specification and certification.