



### OT25 Wood-flex Satin Opaque Timber Paint



#### Technical Data

**Pack Size**  
10L

**Colours**  
White & Black

**Application Tool**  
Brush, Roller or Spray

**Suitable Substrates**  
All exterior timber substrates

**Coverage**  
Approximately 14m<sup>2</sup> per litre dependent on the nature and porosity of the surface

**Application Temperature**  
8°C - 25°C for a minimum of 24 hours



Silicone Technology




Satin Finish



Breathable / Microporous



Ultra-Waterproofing



Good Blocking Properties



Excellent Colour Retention

#### DESCRIPTION

WetherTex OT25 Wood-Flex Satin Opaque Timber Paint is a quick drying, high quality opaque satin finish for all exterior timber. Developed using advanced Optilife silicone technology, OT25 is highly breathable and flexible and provides long term colour stability for your timber and total weather protection for up to 12 years.

#### PREPARATION

Ensure all surfaces to be painted are clean, dry and free from grease and loose or flaking material that may impair adhesion. Any faults in the substrate, particularly those that can lead to moisture penetration, must be rectified. If your substrate has been previously painted rub down with a fine waterproof abrasive paper and then rinse thoroughly. Bare substrates should also be abraded to allow improved adhesion. To improve inter-coat adhesion, repeat between all additional coats. Please avoid inhaling any sanding dust and always wear a face mask if fine sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. All surfaces must be clean, dry and free from algae, lichen & other growths. On new or bare timber ensure pretreated with a good quality suitable preservative. On resinous timbers it is recommended to use a suitable wood primer.

#### APPLICATION

Stir the product thoroughly. For the best results apply by brush, roller or spray. Application tool type and quality may influence the finished appearance. Apply liberally and avoid overspreading. Not to be applied below 8°C. Under normal conditions will be dry after 1-2 hours, add additional coats after 3-4 hours. Ensure good ventilation during drying and application. Do not apply externally when rain or other inclement weather is imminent, ensure substrate is dry. It is recommended to apply 2 coats, though more may be required dependent on the nature and porosity of the substrate.

#### STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture. Once you have completed painting ensure you remove as much product as possible from your application tool. If you have any leftover product, ensure that you close the tin by replacing the lid firmly and securely and store in a safe place. Protect from frost. To avoid the risk of spillage, always store and transport in a secure upright position.

#### TOOL CLEANING

All equipment must be washed with clean, cold water immediately after use. Waste material should not be emptied in the drainage systems. Some local authorities have special facilities for the disposal of leftover paint. Please do not add any product into drains or watercourses.

#### HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product by visiting [www.wetherTex.co.uk](http://www.wetherTex.co.uk)

#### IMPORTANT INFORMATION

The environmental climatic conditions for application and drying are critical. The following conditions can negatively affect the product performance and should be avoided, and taken into full consideration in the first 24 hours after application:

- If frost or heavy rain is forecast
- Relative Humidity is above 85%
- In temperatures below 8°C or above +25°C
- If the substrate is hot (at above 30°C) or below +8°C
- Coverage rates are approximate and do not take into account wastage and uneven substrates

If the above is not followed or alternative products are used, then system failure may occur.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.