



# Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

# Protecta FR IPT (plastic cartridge)





The Norwegian EPD Foundation

# Owner of the declaration:

Polyseam AS

#### **Product**

Protecta FR IPT (plastic cartridge)

#### **Declared unit:**

1 kg

# This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core

NPCR 009:2021 Part B for Technical - Chemical products for building and construction industry

#### Program operator:

The Norwegian EPD Foundation

#### **Declaration number:**

NEPD-7633-7008-EN

# Registration number:

NEPD-7633-7008-EN

Issue date: 24.09.2024

Valid to: 24.09.2029

#### **EPD** software:

LCAno EPD generator ID: 563278



#### **General information**

**Product** 

Protecta FR IPT (plastic cartridge)

**Program operator:** 

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway

Phone: +47 977 22 020 web: www.epd-norge.no

**Declaration number:** 

NEPD-7633-7008-EN

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR NPCR 009:2021 Part B for Technical - Chemical products for building and construction industry

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

**Declared unit:** 

1 kg Protecta FR IPT (plastic cartridge)

Declared unit with option:

A1,A2,A3

**Functional unit:** 

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

**Verification of EPD tool:** 

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools. NEPDT73

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

Polyseam AS Contact person: Andrea Bogstad Phone: +47 33 30 67 00 e-mail: post.no@polyseam.com

Manufacturer:

Polyseam Ltd

Place of production:

Polyseam Ltd St Andrews Road 15 HD1 6SB Huddersfield, West Yorkshire, United Kingdom

Management system:

ISO 9001, ISO 14001

Organisation no:

986 426 051

Issue date:

24.09.2024

Valid to:

24.09.2029

Year of study:

2022

**Comparability:** 

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

**Development and verification of EPD:** 

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Andrea Bogstad

Reviewer of company-specific input data and EPD: Wol Hluchan

Approved:

Håkon Hauan

Managing Director of EPD-Norway



#### **Product**

#### **Product description:**

Protecta FR IPT is a high performance, professional quality, one part ready to use sealant and adhesive. Based on an innovative Inert Polymer Technology it is suitable for a wide variety of building trade applications including decorating, flooring, joinery, plumbing and tiling and outperforms conventional silicone, MSP, butyl and acrylic based products as a sealant and adhesive – free from dangerous emissions.

FR IPT is designed for sealing joints, voids/irregular holes in walls, partitions and other structures, resulting in an airtight and watertight seal. IPT is a non-reactive chemistry that ensures compatibility with most building materials and has the unique property of moving dynamically to accommodate the natural or unexpected movements of sealed/bonded joints within a building, for long-lasting performance.

#### **Product specification**

Materials	Value	Unit
MATERIALS		
Pigments	0,25-2	%
Binder	40-50	%
Preservative	0,03	%
Chemical	1-10	%
Mineral	30-60	%
Solvent	10-15	%
PACKAGING		
Packaging - Cardboard	0,03	kg
Packaging - Plastic	0,12	kg
Packaging - Wood	0,04	kg

#### Technical data:

The product has third-party verified ETAs and UKTAs issued in accordance with regulation (EU) No 305/2011 on the basis of EAD 350454-00-1104, tested to EN 1366-3 & -4 in conjunction with EN 1363-1. The product holds the following approval marks; CE-mark for Europe, UKCA-mark for UK, UL-EU Certificate Internationally, UAE Certificate of Compliance & AS assessment for Australia and New Zealand.

For more information, please see https://protecta.co.uk/product/fire-rated-ipt/

#### Market

Global. Transport to market is not included in this EPD.

#### Reference service life, product

The reference service life of the product depends on its application area.

### Reference service life, building

N/A

#### LCA: Calculation rules

## Declared unit:

1 kg Protecta FR IPT (plastic cartridge)

#### **Cut-off criteria:**

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

#### **Allocation:**

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

#### Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.



Materials	Source	Data quality	Year
Binder	ecoinvent 3.6	Database	2019
Binder	Modified ecoinvent 3.6	Database	2019
Chemical	ecoinvent 3.6	Database	2019
Mineral	ecoinvent 3.6	Database	2019
Packaging - Cardboard	Modified ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Wood	Modified ecoinvent 3.6	Database	2019
Pigments	ecoinvent 3.6	Database	2019
Preservative	ecoinvent 3.6	Database	2019
Solvent	ecoinvent 3.6	Database	2019




# System boundaries (X=included, MND=module not declared, MNR=module not relevant)

	Product stage				uction on stage		Use stage			End of I	ife stage		Beyond the system boundaries				
	Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De- construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
İ	A1	A2	A3	A4	A5	B1	B2	В3	В4	B5	В6	В7	C1	C2	C3	C4	D
Ì	Χ	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

#### System boundary:

The life cycle analysis is a cradle-to-gate (A1 - A3) study. It includes the extraction and production of raw materials and packaging, transportation to the manufacturing site, as well as the manufacturing process itself.



#### Additional technical information:

Protecta FR IPT can be removed with a knife/scraper and disposed of at an approved waste facility.

Polyseam's factory is certified according to the ISO 14001 Environmental Management Systems (EMS). It provides a framework for organisations to design and implement an EMS, and continually improve their environmental performance.

Learn more: https://www.polyseam.com/sustainability/



# LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.



#### **LCA: Results**

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmenta	Environmental impact								
	Indicator	Unit	A1	A2	A3				
	GWP-total	kg CO <sub>2</sub> -eq	1,89E+00	1,43E-01	5,40E-02				
	GWP-fossil	kg CO <sub>2</sub> -eq	1,88E+00	1,43E-01	5,23E-02				
	GWP-biogenic	kg CO <sub>2</sub> -eq	5,01E-03	6,80E-05	1,68E-03				
	GWP-luluc	kg CO <sub>2</sub> -eq	1,20E-03	9,53E-05	5,97E-05				
	ODP	kg CFC11 -eq	1,32E-07	3,05E-08	4,67E-09				
	АР	mol H+ -eq	1,03E-02	1,32E-03	1,83E-04				
<del></del>	EP-FreshWater	kg P -eq	6, 18E-05	1,21E-06	1,34E-06				
<del></del>	EP-Marine	kg N -eq	1,39E-03	3,97E-04	3,70E-05				
<del></del>	EP-Terrestial	mol N -eq	1,64E-02	4,39E-03	4,03E-04				
	POCP	kg NMVOC -eq	8,43E-03	1,20E-03	1,05E-04				
	ADP-minerals&metals <sup>1</sup>	kg Sb-eq	4,50E-05	2,83E-06	6,49E-07				
	ADP-fossil <sup>1</sup>	MJ	4,48E+01	2,06E+00	1,07E+00				
<u></u>	WDP <sup>1</sup>	m <sup>3</sup>	7,73E+01	2,04E+00	4,62E+00				

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

# Remarks to environmental impacts

<sup>&</sup>quot;Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009"

<sup>\*</sup>INA Indicator Not Assessed

<sup>1.</sup> The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator



Additional environmental impact indicators								
	Indicator	Unit	A1	A2	A3			
PM		Disease incidence		8,30E-09	7,27E-10			
(100) E	IRP <sup>2</sup>	kgBq U235 -eq	6,33E-02	9,09E-03	1,72E-02			
40	ETP-fw <sup>1</sup>	CTUe	3,06E+01	1,49E+00	7,72E-01			
40.* ******	HTP-c <sup>1</sup>	CTUh	2,46E-09	0,00E+00	1,90E-11			
HTP-nc <sup>1</sup>		CTUh	1,99E-08	1,34E-09	6,56E-10			
	SQP <sup>1</sup>	dimensionless	1,24E+01	1,41E+00	8,97E-01			

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

<sup>&</sup>quot;Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

<sup>1.</sup> The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

<sup>2.</sup> This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.



Resource use								
	Indicator	Unit	A1	A2	A3			
्र (हे	PERE	MJ	2,42E+00	3,20E-02	2,94E-01			
	PERM	MJ	0,00E+00	0,00E+00	0,00E+00			
¥ <b>i</b>	PERT	МЈ	2,42E+00	3,20E-02	2,94E-01			
	PENRE	МЈ	3,45E+01	2,06E+00	1,07E+00			
	PENRM	MJ	6,16E+00	0,00E+00	0,00E+00			
<b>IA</b>	PENRT	MJ	4,07E+01	2,06E+00	1,07E+00			
	SM	kg	4,22E-03	0,00E+00	0,00E+00			
	RSF	MJ	6,64E-02	1,40E-03	4,26E-04			
	NRSF	MJ	1,49E-02	3,90E-03	4,96E-04			
<b>®</b>	FW	m <sup>3</sup>	3,75E-02	2,38E-04	4,30E-04			

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources; SM = Use of secondary materials; PENRM = Use of renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; RSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed



End of life - Waste								
	ndicator	Unit	A1	A2	A3			
	HWD	kg	4,34E-03	1,10E-04	3,21E-03			
Ī	NHWD	kg	1,90E-01	8,00E-02	6,31E-03			
<u> </u>	RWD	kg	6,12E-05	1,41E-05	8,58E-06			

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

End of life - Output flow								
Indicator		Unit	A1	A2	A3			
<b>∅&gt;</b>	CRU	kg	0,00E+00	0,00E+00	0,00E+00			
⇔>	MFR	kg	8,85E-04	0,00E+00	1,10E-02			
D₹	MER	kg	3,46E-05	0,00E+00	8,75E-08			
<b>₹</b>	EEE	MJ	2,81E-04	0,00E+00	8,41E-03			
D	EET	MJ	4,26E-03	0,00E+00	1,27E-01			

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

Biogenic Carbon Content								
Unit	At the factory gate							
kg C	0,00E+00							
kg C	0,00E+00							
	kg C							

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2



# **Additional requirements**

#### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, United Kingdom, Market mix (kWh)	ecoinvent 3.6	386,67	g CO2-eq/kWh
Electricity, United Kingdom, Solar (kWh)	ecoinvent 3.6	78,98	g CO2-eq/kWh

#### **Dangerous substances**

The product contains no substances given by the REACH Candidate list.

#### **Indoor environment**

Protecta FR IPT has been emission tested by Normec Product Testing. Meets the exemplary level criteria for indoor air quality as specified in the BREEAM UK New Construction Manual 2023 v6.1.

#### **Additional Environmental Information**

Additional environmental impact indicators required in NPCR Part A for construction products							
Indicator	Unit	A1	A2	A3			
GWPIOBC	kg CO <sub>2</sub> -eq	1,88E+00	1,43E-01	6,15E-02			

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.



# **Bibliography**

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012 + A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, (2019) Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21 Graafland, J. and Ruttenborg, M. (2023) EPD generator for NPCR009:2021, Part B for Technical - Chemical products (non-cement based products), Background information for EPD generator application and LCA data, LCA.no report number: 12.23.

NPCR Part A: Construction products and services. Ver. 2.0, 24.03.2021 EPD Norway.

NPCR 009 Part B for Technical - Chemical products for building and construction industry, Ver. 3.0, 06.10.2021, EPD Norway.

SPT2023-R071 - VOC Emission Test Report

@ and narga	Program operator and publisher	Phone: +47 977 22 020
© epd-norge	The Norwegian EPD Foundation	e-mail: post@epd-norge.no
Global program operatør	Post Box 5250 Majorstuen, 0303 Oslo, Norway	web: www.epd-norge.no
	Owner of the declaration:	Phone: +47 33 30 67 00
'Polyseam.	Polyseam AS	e-mail: post.no@polyseam.com
ď	Ravneveien 7, 3174 Revetal	web: https://www.polyseam.com/
	Author of the Life Cycle Assessment	Phone: +47 916 50 916
(LCA)	LCA.no AS	e-mail: post@lca.no
	Dokka 6A, 1671 Kråkerøy	web: www.lca.no
	Developer of EPD generator	Phone: +47 916 50 916
(LCA)	LCA.no AS	e-mail: post@lca.no
.no	Dokka 6A, 1671 Kråkerøy	web: www.lca.no
EGO PLATFORM	ECO Platform	web: www.eco-platform.org
VERIFIED	ECO Portal	web: ECO Portal